NSN 5320-00-689-7212

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-689-7212 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.974 inches and 0.999 inches **Head Style:** Err-090 **Head Height:** Between 0.141 inches and 0.153 inches **Shank Diameter:** 0.3273 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.537 inches and 0.549 inches Tip Diameter: 0.3189 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.490 inches and 0.505 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 8740 or steel comp e4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-00-689-7212

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.