NSN 5320-00-689-7405

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-689-7405 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.315 inches and 1.333 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.189 inches and 0.190 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches **Grip Length:** 1.005 inches Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 125000 single pounds per square inch **Special Features:** Cetyl alcohol lube 305 73197 Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5320-00-689-7405

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.