# NSN 5320-00-701-9809

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-701-9809



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.614 inches and 0.634 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.037 inches and 0.047 inches

### Width Between Flats:

Between 0.0791 inches and 0.0801 inches

#### Shank Diameter:

Between 0.1625 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.242 inches and 0.262 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

Between 0.307 inches and 0.317 inches

### Thready Qty Per Inch (tpi):

32

### **Thread Size:**

0.164 inches

# Material:

Steel comp 431

### **Material Specification:**

Ams 5628 assn standard single material response or mil-s-18732 military specification single material response

#### Surface Treatment:

Passivate

### Surface Treatment Specification:

Hi-shear specification 258, cagec 73197 mfr ref single treatment response

# Thread Series Designator:

Unjc

# Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-00-701-9809

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

