

View Online at <https://aerobasegroup.com/nsn/5320-00-701-9809>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.614 inches and 0.634 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.037 inches and 0.047 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0801 inches

**Shank Diameter:**

Between 0.1625 inches and 0.1635 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.242 inches and 0.262 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.307 inches and 0.317 inches

**Thread Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Material:**

Steel comp 431

**Material Specification:**

Ams 5628 assn standard single material response or mil-s-18732 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Hi-shear specification 258, cagc 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-18732 spec.