NSN 5320-00-702-3221

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-702-3221

Fastener Length:
Between 2.940 inches and 3.140 inches
Head Style:
Err-090
Head Height:
Between 0.099 inches and 0.111 inches
Shank Diameter:
Between 0.188 inches and 0.190 inches
Shank Style:
Pin-rivet, multiple grooved
Head Major Diameter:
Between 0.297 inches and 0.327 inches
Grip Length:
Between 0.845 inches and 0.906 inches
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Material: Steel
Steel
Steel Surface Treatment:
Steel Surface Treatment: Cadmium
Steel Surface Treatment: Cadmium Surface Treatment Specification:
Steel Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response
Steel Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life:
Steel Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a
Steel Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:
Steel Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:
Steel Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:
Steel Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No
Steel Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: