

View Online at <https://aerobasegroup.com/nsn/5320-00-717-9746>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.690 inches and 0.710 inches

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

0.079 mils and 0.081 centimeters

Shank Diameter:

Between 0.1880 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.380 centimeters

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

160000 single pounds per square inch

Material:

Steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.