NSN 5320-00-720-8854

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-720-8854

View Online at https://aerobasegroup.com/nsn/5320-00-720-8854
Fastener Length:
Between 1.196 inches and 1.226 inches
Head Style:
Hexagon countersunk
Head Height:
Between 0.072 inches and 0.079 inches
Shank Diameter:
Between 0.258 inches and 0.260 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Expansion Device:
Serrated stem-type w
Lubrication:
Dry film or wax
Grip Length:
Between 0.969 inches and 1.031 inches
Width Across Flats:
Between 0.458 inches and 0.472 inches
Min. Tensile Strength (psi):
180000 pounds per square inch
Shear Strength:
5300 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Heat Treatment:
Annealed
Material:
Steel comp 4130 stem or steel comp 8740 stem or steel comp 4140 stem
Material Specification:
Qq-a-282 federal specification single material response body
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A040a0

NSN 5320-00-720-8854

Blind Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.