

View Online at <https://aerobasegroup.com/nsn/5320-00-722-2912>

Fastener Length:

Between 0.766 inches and 0.796 inches

Head Style:

Hexagon

Head Height:

0.160 inches

Shank Diameter:

Between 0.309 inches and 0.311 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded mandrel

Grip Length:

Between 0.595 inches and 0.656 inches

Width Across Flats:

Between 0.429 inches and 0.437 inches

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Material:

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Specification Data:

80205-nas1669 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.