

View Online at <https://aerobasegroup.com/nsn/5320-00-728-8481>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.190 inches and 1.210 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.095 inches and 0.097 inches

Shank Diameter:

Between 0.249 inches and 0.250 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.390 inches and 0.395 inches

Grip Length:

0.775 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.