

View Online at <https://aerobasegroup.com/nsn/5320-00-728-8533>

**Head Style:**

Hexagon

**Head Height:**

0.113 inches

**Shank Diameter:**

Between 0.1970 inches and 0.1990 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Threaded stem

**Lubrication:**

Wax or cetyl alcohol

**Grip Length:**

Between 0.595 inches and 0.656 inches

**Width Across Flats:**

Between 0.305 inches and 0.312 inches

**Material:**

Iron alloy 660 boltiron alloy 660 nutiron alloy 660 sleeve

**Material Specification:**

Ams 5735 assn standard single material response bolt or ams 5737 assn standard single material response boltams 5735 assn standard single material response nut or ams 5737 assn standard single material response nutams 5735 assn standard single material response sleeve or ams 5737 assn standard single material response sleeve

**Surface Treatment:**

Passivate boltpassivate nutpassivate sleeve

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response boltmil-s-5002 military specification single treatment response nutmil-s-5002 military specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5002 spec.