NSN 5320-00-731-6152

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-731-6152 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.255 inches and 0.257 inches **Shank Style:** Blind rivet, nut and bolt (assembly) **Head Major Diameter:** Between 0.312 inches and 0.317 inches **Expansion Device:** Threaded stem and expander **Grip Length:** 0.0625 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** Between 98.0 degrees and 102.0 degrees **Special Features:** Furnished without bolt **Heat Treatment:** Annealed sleeve Material: Steel comp 431 sleeve or steel comp 302 sleeve or steel comp xm-7 sleeve **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or astma493 assn standard 2nd material response sleeve or ams a493 assn standard 3rd material response sleeve **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

Fiig:

A040a0