

View Online at <https://aerobasegroup.com/nsn/5320-00-732-0187>

**Fastener Length:**

Between 3.220 inches and 3.420 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.248 inches and 0.249 inches

**Shank Style:**

Pin-riquet, multiple grooved

**Head Major Diameter:**

Between 0.344 inches and 0.399 inches

**Grip Length:**

Between 1.626 inches and 1.688 inches

**Features Provided:**

Casehardened

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

37.0 rockwell c and 41.0 rockwell c

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 4130 or steel comp 6150 or steel comp 4037

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6758 military specification 4th material response or mil-s-8503 military specification 5th material response or mil-s-8695 military specification 6th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Specification Data:**

80205-nas 1438 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5626 spec.