

View Online at <https://aerobasegroup.com/nsn/5320-00-732-0187>

Fastener Length:

Between 3.220 inches and 3.420 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.248 inches and 0.249 inches

Shank Style:

Pin-rivet, multiple grooved

Head Major Diameter:

Between 0.344 inches and 0.399 inches

Grip Length:

Between 1.626 inches and 1.688 inches

Features Provided:

Casehardened

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

37.0 rockwell c and 41.0 rockwell c

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 4130 or steel comp 6150 or steel comp 4037

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6758 military specification 4th material response or mil-s-8503 military specification 5th material response or mil-s-8695 military specification 6th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Specification Data:

80205-nas 1438 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.