NSN 5320-00-732-1443

Blind Rivet - Page 1 of 1

A040a0



View Online at https://aerobasegroup.com/nsn/5320-00-732-1443

View Online at https://aerobasegroup.com/nsn/5320-00-732-1443
Fastener Length:
Between 0.338 inches and 0.368 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.197 inches and 0.199 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
Between 0.378 inches and 0.385 inches
Expansion Device:
Serrated stem-type w
Lubrication:
Dry film or paraffin wax
Grip Length:
Between 0.219 inches and 0.281 inches
Hardness Rating:
30.0 rockwell c nut and 45.0 rockwell c nut
Shear Strength:
4530 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Iron alloy 660 sleeve
Material Specification:
Ams 5737 assn standard single material response sleeve or ams 5732 assn standard single material response sleeve
Surface Treatment:
Passivate sleeve
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response sleeve
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: