NSN 5320-00-753-3942

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-753-3942

Fastener Length:

Between 0.118 inches and 0.132 inches

Head Style:

Oval/truss

Head Height:

Between 0.020 inches and 0.026 inches

Hole Diameter:

Between 0.062 inches and 0.066 inches

Shank Diameter:

Between 0.085 inches and 0.089 inches

Shank Style:

Tubular

Head Major Diameter:

Between 0.142 inches and 0.152 inches

Hole Depth:

Between 0.047 inches and 0.078 inches

Shear Strength:

32000 double pounds per square inch

Material:

Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Specification Or Standard:

12 type and 3 class and e grade

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0