

View Online at <https://aerobasegroup.com/nsn/5320-00-758-8397>

Fastener Length:

Between 0.672 inches and 0.702 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.310 inches and 0.312 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.635 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.500 inches and 0.562 inches

Hardness Rating:

30.0 rockwell c and 45.0 rockwell c

Shear Strength:

10350 double pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

Material Specification:

Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-6049 military specification 3rd material response nut

Surface Treatment:

Passivate sleeve or cadmium sleeve

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.