NSN 5320-00-758-8397

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-758-8397

3
Fastener Length:
Between 0.672 inches and 0.702 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.310 inches and 0.312 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
0.635 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.500 inches and 0.562 inches
Hardness Rating:
30.0 rockwell c and 45.0 rockwell c
Shear Strength:
10350 double pounds per square inch
Countersink Angle:
100.0 degrees
Material:
Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut
Material Specification:
Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-6049 military
specification 3rd material response nut
Surface Treatment:
Passivate sleeve or cadmium sleeve
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response nut
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-s-6758 spec.