

View Online at <https://aerobasegroup.com/nsn/5320-00-759-3368>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.865 inches and 0.885 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.127 inches and 0.130 inches

**Shank Diameter:**

Between 0.311 inches and 0.312 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.629 inches and 0.634 inches

**Grip Length:**

0.380 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.312 inches

**Countersink Angle:**

100.0 degrees

**Material:**

Steel

**Material Specification:**

Mil-s-6049 military specification single material response or mil-s-5626 military specification single material response or mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.