NSN 5320-00-759-6360

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-759-6360 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 3.130 inches and 3.255 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.263 inches and 0.265 inches Shank Style: Pin-rivet, multiple grooved **Head Major Diameter:** 0.507 inches Lubrication: Cetyl alcohol **Grip Length:** Between 2.126 inches and 2.188 inches Thready Qty Per Inch (tpi): 48 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.216 inches **Shear Strength:** 108000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 8740 **Material Specification:** Aisi assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:**

Uns
Shelf Life:
N/a
Unit Of Measure:
--

NSN 5320-00-759-6360

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0