NSN 5320-00-759-6360

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-759-6360



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 3.130 inches and 3.255 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.263 inches and 0.265 inches

Shank Style:

Pin-rivet, multiple grooved

Head Major Diameter:

0.507 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 2.126 inches and 2.188 inches

Thready Qty Per Inch (tpi):

48

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.216 inches

Shear Strength:

108000 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 8740

Material Specification:

Aisi assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-00-759-6360

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

