

View Online at <https://aerobasegroup.com/nsn/5320-00-781-0485>

Fastener Length:

Between 0.276 inches and 0.306 inches

Head Style:

Hexagon

Head Height:

Between 0.100 inches and 0.116 inches

Shank Diameter:

Between 0.197 inches and 0.199 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded mandrel

Grip Length:

Between 0.156 inches and 0.219 inches

Width Across Flats:

Between 0.302 inches and 0.312 inches

Shear Strength:

5240 double pounds per square inch

Heat Treatment:

Annealed

Material:

Steel comp 8740 nut or steel comp 4130 nut or steel comp 4340 nut

Material Specification:

Mil-s-6049 military specification single material response nut or ams 6322 assn standard single material response nut or mil-s-6758 military specification single material response nut or mil-s-5000 military specification single material response nut

Surface Treatment:

Passivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response bolt

Specification Data:

81205-bacb30cc manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.