

View Online at <https://aerobasegroup.com/nsn/5320-00-781-8609>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.258 inches and 0.260 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.507 inches

Expansion Device:

Threaded stem

Grip Length:

Between 0.470 inches and 0.531 inches

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Shear Strength:

9000 double pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response nut

Specification Data:

80205-nas1670 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.