

View Online at <https://aerobasegroup.com/nsn/5320-00-782-7568>

Fastener Length:

Between 0.829 inches and 0.859 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.311 inches and 0.312 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.626 inches and 0.635 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Grease film

Grip Length:

Between 0.657 inches and 0.769 inches

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Shear Strength:

146000 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Heat Treatment:

Annealed

Material:

Steel comp 8740 stem

Material Specification:

Mil-s-6049 military specification single material response stem

Surface Treatment:

Cadmium sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.