

View Online at <https://aerobasegroup.com/nsn/5320-00-793-5513>

**Fastener Length:**

Between 0.678 inches and 0.698 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.124 inches and 0.128 inches

**Shank Style:**

Straight w/radius chamfered tip

**Head Major Diameter:**

Between 0.221 inches and 0.229 inches

**Grip Length:**

0.490 mils and 0.510 centimeters

**Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

**Material:**

Aluminum alloy 1100 or aluminum alloy 5056 or aluminum alloy 2117 or aluminum alloy 2024 or aluminum alloy 2017

**Material Specification:**

Qq-a-430, alloy 1100 federal specification single material response or qq-a-430, alloy 5056 federal specification single material response or qq-a-430, alloy 2024 federal specification single material response or qq-a-430, alloy 2017 federal specification single material response or qq-a-430, alloy 2117 federal specification single material response

**Surface Treatment:**

Anodize or chromate

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.