

View Online at <https://aerobasegroup.com/nsn/5320-00-793-5513>

Fastener Length:

Between 0.678 inches and 0.698 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.124 inches and 0.128 inches

Shank Style:

Straight w/radius chamfered tip

Head Major Diameter:

Between 0.221 inches and 0.229 inches

Grip Length:

0.490 mils and 0.510 centimeters

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Material:

Aluminum alloy 1100 or aluminum alloy 5056 or aluminum alloy 2117 or aluminum alloy 2024 or aluminum alloy 2017

Material Specification:

Qq-a-430, alloy 1100 federal specification single material response or qq-a-430, alloy 5056 federal specification single material response or qq-a-430, alloy 2024 federal specification single material response or qq-a-430, alloy 2017 federal specification single material response or qq-a-430, alloy 2117 federal specification single material response

Surface Treatment:

Anodize or chromate

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.