## NSN 5320-00-797-1495

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-797-1495



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.115 inches and 1.135 inches

## Head Style:

Err-090

## Head Height:

Between 0.068 inches and 0.078 inches

### Width Between Flats:

Between 0.127 inches and 0.130 inches

### Shank Diameter:

Between 0.311 inches and 0.312 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.475 inches and 0.505 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.620 inches and 0.630 inches

## Thread Size:

0.312 inches

## Shear Strength:

19160 double pounds per square inch

Material:

Steel comp 431

## **Material Specification:**

Mil-s-18732 military specification single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-00-797-1495

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

