## NSN 5320-00-797-1501

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-797-1501



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.947 inches and 0.967 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.092 inches and 0.097 inches

#### Shank Diameter:

Between 0.249 inches and 0.250 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

#### Lubrication:

Cetyl alcohol

#### Grip Length:

Between 0.557 inches and 0.567 inches

#### Thread Size:

0.250 inches

#### Shear Strength:

12260 double pounds per square inch

#### Material:

Steel comp 431

#### **Material Specification:**

Mil-s-18732 military specification single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-00-797-1501

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

