## NSN 5320-00-804-4393

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-804-4393

| Fastener Length:  |
|---|
| Between 0.490 inches and 0.510 inches                                     |
| Head Style:   |
| Universal   |
| Head Height:  |
| Between 0.107 inches and 0.117 inches                                     |
| Shank Diameter:   |
| Between 0.280 inches and 0.285 inches                                     |
| Shank Style:  |
| Straight  |
| Head Major Diameter:  |
| Between 0.475 inches and 0.525 inches                                     |
| Shear Strength:   |
| 33000 single pounds per square inch                                       |
| Material:   |
| Aluminum alloy 2017   |
| Material Specification:   |
| Qq-a-430 federal specification single material response                   |
| Surface Treatment:  |
| Anodize   |
| Surface Treatment Specification:  |
| Mil-a-8625, type 2, cl 1 military specification single treatment response |
| Specification Data:   |
| 81205-bacr15wd manufacturers standard                                     |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A040a0  |
| Mil-std (military Standard):  |
| Mil-a-8625 spec.  |
|   |
|   |