

View Online at <https://aerobasegroup.com/nsn/5320-00-809-1923>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.1625 inches and 0.1645 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

0.164 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.720 inches and 0.781 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4140 bolt or steel comp 8740 bolt or steel comp 4130 boltsteel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nutsteel comp 304 sleeve or steel comp 303se sleeve

**Material Specification:**

Mil-s-5626 military specification 1st material response bolt or mil-s-6049 military specification 2nd material response bolt or mil-s-6758 military specification 3rd material response boltmil-s-5626 military specification 1st material response nut or mil-s-6049 military specification 1st material response nut or mil-s-6758 military specification 3rd material response nutams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve

**Surface Treatment:**

Cadmium bolt and chromate boltcadmium nut and chromate nutpassivate sleeve and cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416 ty ii cl 2 federal specification single treatment response boltqq-p-416 ty ii cl 2 federal specification single treatment response nutmil-s-5002 military specification 1st treatment response sleeve and qq-p-416 ty i cl 3 federal specification 2nd treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.