

View Online at <https://aerobasegroup.com/nsn/5320-00-809-2163>

Head Style:

Hexagon

Head Height:

0.160 inches

Shank Diameter:

Between 0.3095 inches and 0.3115 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded stem

Grip Length:

Between 0.282 inches and 0.344 inches

Width Across Flats:

Between 0.429 inches and 0.437 inches

Material:

Steel comp 4140 bolt or steel comp 8740 bolt or steel comp 303se boltsteel comp 4140 nut or steel comp 8740 nut or steel comp 303se nutsteel comp 303 sleeve or steel comp 304 sleeve or steel comp 303se sleeve

Material Specification:

Mil-s-5626 military specification 1st material response bolt or mil-s-6049 military specification 2nd material response bolt or mil-s-6758 military specification 3rd material response boltmil-s-5626 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-6758 military specification 3rd material response nutjq-q-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium bolt and chromate boltcadmium nut and chromate nutpassivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416 ty ii cl 2 federal specification single treatment response boltqq-p-416 ty ii cl 2 federal specification single treatment response nutmil-s-5002 military specification 1st treatment response sleeve and qq-p-416 ty i cl 3 federal specification 2nd treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.