NSN 5320-00-813-6313

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-813-6313

Fastener Length:
0.836 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.258 inches and 0.260 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.507 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.406 inches and 0.470 inches
Hardness Rating:
48.0 rockwell c stem and 53.0 rockwell c stem
Shear Strength:
5900 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Mechanical lock steel aisi 660; mechanical lock steel, qq-s-633 comp c1144
Material:
Steel comp 8740 stem
Material Specification:
Qq-w-405 federal specification 1st material response body or qq-w-405 federal specification 2nd material response body or mil-s-6758
military specification 2nd material response body
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416, type 2, cl3 federal specification single treatment response mechanical lock
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-s-6049 spec.