

View Online at <https://aerobasegroup.com/nsn/5320-00-814-1184>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.740 inches and 0.760 inches

Head Style:

Err-090

Head Height:

Between 0.055 inches and 0.060 inches

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.163 inches and 0.164 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.306 inches and 0.322 inches

Grip Length:

0.443 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.164 inches

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.