NSN 5320-00-814-2525

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-814-2525

| Fastener Length: |
|--|
| 1.398 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.258 inches and 0.260 inches |
| Shank Style: |
| Self-plugging mechanically locked stem |
| Head Major Diameter: |
| 0.507 inches |
| Expansion Device: |
| Serrated stem-type w |
| Grip Length: |
| Between 0.969 inches and 1.032 inches |
| Hardness Rating: |
| 48.0 rockwell c bolt and 53.0 rockwell c bolt |
| Shear Strength: |
| 5900 single pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel mechanical lock |
| Material Specification: |
| Ams 5737 assn standard single material response mechanical lock |
| Surface Treatment: |
| Cadmium sleeve and chromate sleeve |
| Surface Treatment Specification: |
| Qq-p-416 type 2 federal specification single treatment response mechanical lock |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| |
| |