

View Online at <https://aerobasegroup.com/nsn/5320-00-814-3267>

Fastener Length:

Between 0.652 inches and 0.682 inches

Head Style:

Hexagon

Head Height:

Between 0.180 inches and 0.190 inches

Shank Diameter:

Between 0.373 inches and 0.375 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film or wax

Grip Length:

Between 0.406 inches and 0.469 inches

Width Across Flats:

Between 0.491 inches and 0.500 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Special Features:

Heat process mil-h-6875

Heat Treatment:

Annealed

Material:

Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut

Material Specification:

Mil-s-5626 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-6758 military specification 3rd material response nut

Surface Treatment:

Passivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.