NSN 5320-00-814-8559

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-814-8559 **Fastener Length:** 0.855 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Head Height:** 0.080 inches **Shank Diameter:** Between 0.213 inches and 0.215 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Head Major Diameter:** Between 0.342 inches and 0.385 inches **Expansion Device:** Threaded mandrel **Grip Length:** Between 0.719 inches and 0.781 inches Hardness Rating: 39.0 rockwell c nut and 43.0 rockwell c nut **Countersink Angle:** 100.0 degrees Material: Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve **Surface Treatment:** Cadmium sleeve and chromate sleeve and passivate sleeve **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response nut Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

Fiig: A040a0

Mil-std (military Standard):

Mil-s-5626 spec.