NSN 5320-00-817-0728

Qq-p-416, type 2, cl 2 federal specification single treatment response

Specification Or Standard:
12 type and 3 class and e grade

Shelf Life:

Unit Of Measure:

Demilitarization:

N/a

No Fiig: A040a0

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-817-0728 **Fastener Length:** Between 0.149 inches and 0.163 inches **Head Style:** Oval/truss **Head Height:** Between 0.020 inches and 0.026 inches **Hole Diameter:** Between 0.062 inches and 0.066 inches **Shank Diameter:** Between 0.085 inches and 0.089 inches **Shank Style:** Tubular **Head Major Diameter:** Between 0.142 inches and 0.152 inches **Hole Depth:** Between 0.047 inches and 0.078 inches **Shear Strength:** 32000 double pounds per square inch Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:**