# NSN 5320-00-817-0847

View Online at https://aerobasegroup.com/nsn/5320-00-817-0847

Pin-rivet - Page 1 of 1



Head Style:

Err-090

# **Head Height:**

Between 0.037 inches and 0.047 inches

# Shank Diameter:

Between 0.155 inches and 0.157 inches

# Shank Style:

Err-090

# Head Major Diameter:

Between 0.242 inches and 0.262 inches

# Grip Length:

0.500 inches

# Min. Tensile Strength (psi):

160000 pounds per square inch

# Material:

Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 4037 or steel comp 4130

# **Material Specification:**

Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-5626 military specification 4th material response or mil-s-5000 military specification 5th material response or mil-s-5000 military specification 6th material response or ams 6300 assn standard 7th material response or mil-s-6758 military specification 8th material response

# Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

# **Specification Data:**

80205-nas1054 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

```
--
```

# Demilitarization:

No

Fiig:

# A528u0

Mil-std (military Standard):

Mil-s-6098 spec.