NSN 5320-00-820-7283

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-820-7283

Head Style:

Hexagon

Head Height:

0.096 inches

Shank Diameter:

Between 0.1625 inches and 0.1645 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded stem

Lubrication:

Wax or cetyl alcohol

Grip Length:

Between 0.157 inches and 0.219 inches

Width Across Flats:

Between 0.244 inches and 0.250 inches

Material:

Iron alloy 660 boltiron alloy 660 nutiron alloy 660 sleeve

Material Specification:

Ams 5735 assn standard single material response bolt or ams 5737 assn standard single material response boltams 5735 assn standard single material response nut or ams 5737 assn standard single material response nutams 5735 assn standard single material response sleeve or ams 5737 assn standard single material response sleeve

Surface Treatment:

Passivate boltpassivate nutpassivate sleeve

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response boltmil-s-5002 military specification single treatment response nutmil-s-5002 military specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

```
Fiig:
```

A040a0

Mil-std (military Standard):

Mil-s-5002 spec.