

View Online at <https://aerobasegroup.com/nsn/5320-00-828-6116>

Fastener Length:

Between 0.333 inches and 0.353 inches

Head Style:

Universal

Head Height:

Between 0.107 inches and 0.117 inches

Shank Diameter:

Between 0.249 inches and 0.253 inches

Shank Style:

Drive pin

Head Major Diameter:

Between 0.475 inches and 0.525 inches

Expansion Device:

Drive stem-type h

Grip Length:

Between 0.203 inches and 0.234 inches

Material:

Steel comp 301 stem or steel comp 302b stem or steel comp 302 stem or steel comp 303 stem or steel comp 303se stem or steel comp 304 stem or steel comp 304l stem or steel comp 305 stem or steel comp 308 stem or steel comp 309 stem or steel comp 309s stem or steel comp 310 stem or steel comp 310s stem or steel comp 314 stem or steel comp 316 stem or steel comp 316l stem or steel comp 317 stem or steel comp 321 stem or steel comp 347 stem or steel comp 348 stem or steel comp 384 stem or steel comp 385 stem or steel stem

Material Specification:

66 federal standard all material responses sleeve

Surface Treatment:

Passivate stem

Surface Treatment Specification:

Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0