

View Online at <https://aerobasegroup.com/nsn/5320-00-835-2195>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.753 inches and 0.773 inches

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.079 inches and 0.081 inches

Shank Diameter:

Between 0.202 inches and 0.203 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.758 inches and 0.778 inches

Lubrication:

Cetyl alcohol

End Application:

W/s: helicopter, hh-53h pave low; aircraft, starlifter c-141; helicopter, iroquois hh/uh-1; helicopter, iroquois uh-1; aircraft, thunderbolt ii, a-10; helicopter, mh-53e; aircraft (ac-130h, mc-130h, ec-130e, hc-130); aircraft, stratolifter c-135; joint stars target radar system; helicopter, green giant h-3

Grip Length:

0.443 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.