

View Online at <https://aerobasegroup.com/nsn/5320-00-835-2195>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.753 inches and 0.773 inches

**Head Height:**

Between 0.064 inches and 0.074 inches

**Width Between Flats:**

Between 0.079 inches and 0.081 inches

**Shank Diameter:**

Between 0.202 inches and 0.203 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.758 inches and 0.778 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

W/s: helicopter, hh-53h pave low; aircraft, starlifter c-141; helicopter, iroquois hh/uh-1; helicopter, iroquois uh-1; aircraft, thunderbolt ii, a-10; helicopter, mh-53e; aircraft (ac-130h, mc-130h, ec-130e, hc-130); aircraft, stratolifter c-135; joint stars target radar system; helicopter, green giant h-3

**Grip Length:**

0.443 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.190 inches

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6758 spec.