

View Online at <https://aerobasegroup.com/nsn/5320-00-837-4908>

Fastener Length:

Between 0.464 inches and 0.494 inches

Head Style:

Hexagon

Head Height:

Between 0.180 inches and 0.190 inches

Shank Diameter:

Between 0.373 inches and 0.375 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film or wax

Grip Length:

Between 0.219 inches and 0.281 inches

Width Across Flats:

Between 0.491 inches and 0.500 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Shear Strength:

19500 double pounds per square inch

Special Features:

Heat process mil-h-6875

Heat Treatment:

Annealed

Material:

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.