## NSN 5320-00-839-3310

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-839-3310

| Fastener Length:   |
|--|
| Between 0.325 inches and 0.345 inches  |
| Head Style:  |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Hole Diameter:   |
| Between 0.060 inches and 0.065 inches  |
| Shank Diameter:  |
| Between 0.123 inches and 0.127 inches  |
| Shank Style:   |
| Tubular  |
| Head Major Diameter:   |
| 0.127 inches   |
| Hole Depth:  |
| Between 0.115 inches and 0.145 inches  |
| Countersink Angle:   |
| 100.0 degrees  |
| Heat Treatment:  |
| As fabricated  |
| Material:  |
| Steel  |
| Material Specification:  |
| Ams 7225 mfr ref single material response  |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:   |
| Ams 2400 mfr ref single treatment response   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |
|  |