

View Online at <https://aerobasegroup.com/nsn/5320-00-840-6241>

**Fastener Length:**

0.168 inches

**Head Style:**

Hexagon

**Head Height:**

0.113 inches

**Shank Diameter:**

Between 0.197 inches and 0.199 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Threaded mandrel

**Grip Length:**

Between 0.031 inches and 0.093 inches

**Width Across Flats:**

Between 0.332 inches and 0.346 inches

**Material:**

Steel comp 304 sleeve or steel comp 303 sleeve or steel comp 303f sleeve

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or astm a582 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

**Surface Treatment:**

Cadmium sleeve and chromate sleeve and passivate sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl2 federal specification 1st treatment response sleeve and qq-p-35 federal specification 2nd treatment response sleeve

**Specification Data:**

80205-nas1673 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.