NSN 5320-00-855-1457

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-855-1457

0.375 inches Head Style: Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.124 inches and 0.128 inches Shank Style: Straight Head Major Diameter: Between 0.221 inches and 0.229 inches
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.124 inches and 0.128 inches Shank Style: Straight Head Major Diameter: Between 0.221 inches and 0.229 inches
Shank Diameter: Between 0.124 inches and 0.128 inches Shank Style: Straight Head Major Diameter: Between 0.221 inches and 0.229 inches
Between 0.124 inches and 0.128 inches Shank Style: Straight Head Major Diameter: Between 0.221 inches and 0.229 inches
Shank Style: Straight Head Major Diameter: Between 0.221 inches and 0.229 inches
Straight Head Major Diameter: Between 0.221 inches and 0.229 inches
Head Major Diameter: Between 0.221 inches and 0.229 inches
Between 0.221 inches and 0.229 inches
Countersink Angle:
Between 99.0 degrees and 100.5 degrees
Material:
Aluminum alloy
Material Specification:
Fms-0116, com+2219-t81 or t6 general dynamics corporation military specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
spec.