

View Online at <https://aerobasegroup.com/nsn/5320-00-866-4646>

**Fastener Length:**

0.344 inches

**Head Style:**

Small pan

**Head Height:**

Between 0.130 inches and 0.140 inches

**Shank Diameter:**

Between 0.258 inches and 0.260 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.400 inches and 0.432 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.094 inches and 0.157 inches

**Min. Tensile Strength (psi):**

112000 pounds per square inch

**Hardness Rating:**

48.0 rockwell c stem and 53.0 rockwell c stem

**Shear Strength:**

5900 single pounds per square inch

**Material:**

Steel comp 4027 sleeve or steel comp 4037 sleeve or steel comp 4130 sleeve

**Material Specification:**

Mil-s-6049 military specification single material response stem or astm a547 assn standard single material response stem

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6049 spec.