NSN 5320-00-866-4652

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-866-4652 **Fastener Length:** 0.740 inches **Head Style:** Small pan **Head Height:** Between 0.125 inches and 0.135 inches **Shank Diameter:** Between 0.197 inches and 0.199 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.305 inches and 0.332 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.531 inches and 0.595 inches Min. Tensile Strength (psi): 112000 pounds per square inch **Hardness Rating:** 48.0 rockwell c stem and 53.0 rockwell c stem **Shear Strength:** 3450 single pounds per square inch Material: Steel comp 8740 stem **Material Specification:** 66 federal standard 1st material response sleeve or astm a547 assn standard 2nd material response sleeve or 66 federal standard 3rd material response sleeve or mil-s-6758 military specification 3rd material response sleeve **Surface Treatment:** Cadmium stem **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Mil-std (military Standard): Mil-s-6758 spec.

Fiig: A040a0