

View Online at <https://aerobasegroup.com/nsn/5320-00-866-4655>

Fastener Length:

1.290 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.163 inches and 0.164 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.762 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.719 inches and 0.782 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Shear Strength:

12200 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Mechanical lock steel aisi 660, steel qq-s-633 comp c1144

Material:

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.