NSN 5320-00-866-4659



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-00-866-4659 Fastener Length: 0.475 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.197 inches and 0.199 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** 0.386 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.094 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem **Shear Strength:** 3450 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Mechanical lock steel aisi 660, steel qq-s-633 c1144 Material: Steel comp 8740 stem **Material Specification:** Qq-w-405 federal specification 1st material response body or qq-w-405 federal specification 2nd material response body or mil-s-6758 military specification 2nd material response body **Surface Treatment:** Cadmium stem **Surface Treatment Specification:** Qq-p-416, type 2, cl3 federal specification single treatment response mechanical lock

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.