NSN 5320-00-866-4668

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-866-4668

Fastener Length:

0.838 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.310 inches and 0.312 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.634 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.344 inches and 0.407 inches

Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

Shear Strength:

8500 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Mechanical lock steel aisi 660, steel qq-s-633 comp c1144

Material:

Steel comp 8740 stem

Material Specification:

Qq-w-405 federal specification 1st material response body or qq-w-405 federal specification 2nd material response body or mil-s-6758

military specification 2nd material response body

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, type 2, cl3 federal specification single treatment response mechanical lock

Shelf Life:

N/a

Unit Of Measure:

```
Demilitarization:
```

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.